



Protectimus Two



Protectimus Crystal

Dimension	62 × 29 × 11 mm	44.3 × 19.9 × 7.4 mm
Weight	~ 15 g	~ 9 g
User Interface	6 / 8 character high contrast LCD display, Built-in button	
Algorithm	OATH compliant time-based TOTP	
Memory Type	Random Access Memory (RAM)	
Battery Lifecycle	5 years (under normal usage) / More than 14,000 clicks	
Power Consumption	Less than 0.01 mW	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)	
Storage Temperature	-20°C ~ 70°C (-4°F ~ 158°F)	
Humidity	5% ~ 90% without condensation	
Physical Resistance	Tamper evident, IP65 / IP68 (with glue injection)	
Certification & Compliance	OATH TOTP Compliant / RoHS / CE / FCC / WEEE	
Color	Deep Blue	Crystal + Blue
Material	PC + ABS	PET + PC
Serial Number	Barcode and serial number under back side faceplate	Serial number under back side faceplate
Customization	Customizable 6 or 8 digits* Faceplate text and color* Casing color* Serial Number* Industrial and end-user packaging*	Faceplate text and color* Serial Number* Industrial and end-user packaging*

*Require minimum purchase volume